NEW ARRIVALS



JULY 2025

Faucet Lock



This faucet lock has a unique, free-spinning design which secures faucets and hose bibbs from vandalism, unauthorized use, tampering, and water theft. Made of solid brass which prevents rusting and includes two keys. Ideal for commercial and industrial buildings, schools, universities, shopping centers, hospitals, and more.

- No tools required
- Recommended for outdoor faucet use
- Fits on 3/4 hose threads

#60031

10 Oz. Compact Anti-Drip Caulk Gun



This unique caulking gun is the smallest rod-less silicone gun on the market. It fits easily into any toolbox and is simple to maneuver in tight spaces and at challenging angles. You can even use a knife to remove the back of the tube as you work through the caulk, to maintain the compact nature of the tool.

- Features a unique anti-drip mechanism to prevent excess dripping.
- Includes a puncture pin stored in the handle to clear a clogged nozzle
- 12:1 Thrust Ratio
- Fits standard 10 oz cartridges and 310 mL sausage packs

#60068

MONTHLY FAVORITES



Krowne Rotary Waste Drain



- Fits 3-1/2" sink openings
- 1-1/4" overflow outlet with cap
- Stainless steel body
- · Stainless steel ball valve
- Includes vandal resistant screw for strainer
- Approximately 2-3 times the drain rate of a conventional lever waste drain

#99940204 #99940205 Short Handle

Krowne Pre Rinse 1.15 GPM Spray Head



 Dual Spray technology featuring two spray patterns:

Shower Pattern - tight, high powered shower pattern for tough grime removal

Knife Pattern - wide, fan-like pattern for large surface area rinsing

- 360° smooth-swivel functionality
- Ergonomic handle
- Durable valve for extended longevity

#99940178

Scraper Utility Knife



- Transforms from a knife to a scraper with a simple press of the thumb
- Features an integrated paint-can opener and lanyard hole
- Includes 5 ToughBuilt Universal Blades

#96324

50ft Coil Hose



- Female X Male connection
- Operating pressure: 20 to 80 psi
- Burst Pressure: 180 psi
- Temperature Rating: 0 to 40°C

#88000

Chemlink M-1



- Non-slump, applies vertically and overhead
- 100% solids, will not shrink
- Paintable within 24 hours
- 20-minute skin over
- Application at temperatures as low as 32°F (0°C)
- +/- 35% joint movement

Applications: masonry, foam, roofing, metal flashing, most metals, coping wood, skylights, glass, HVAC surfaces, aluminum

#61753 10 07

Blaster Garage Door Lubricant



- · Silicone based
- Teflon fluoropolymer helps reduce friction and wear
- Won't accumulate dust and dirt
- Suitable grease replacement in some instances

#10510







